




Trusted above all.



Standard Sprinklers & Spray Nozzles

Quick Reference Guide | EMEA





Introduction to Standard Sprinklers & Spray Nozzles

Viking is renowned for the development, manufacturing, sales and distribution of excellent fire protection technologies and has been a dependable partner in fire protection for many decades.

The broad product portfolio encompasses innovative and proven system components for water, foam and gas extinguishing systems as well as fire detection systems and is a reflection of Viking's unwavering focus on providing customers with the finest products and highest level of support.

Through Viking's dedicated and knowledgeable customer service, installers of fixed fire protection systems have access to those quality products and can place their trust in the professional and dedicated support services provided by Viking employees. From the smallest project to the largest endeavour, Viking is their single-point partner with the goal to provide the right material whenever and wherever needed.

Viking is passionate about fire protection and committed to the growth of the fixed fire protection industry. As Viking is completely focused and dedicated to this market, customers can have confidence that Viking has the expertise that they need to be successful. They can count on Viking's resources and technical expertise to help them whenever they have a challenge to overcome. And they can be sure to find the right product or solution for their project with the necessary approval or accreditation.

This quick reference guide provides an overview of Viking's comprehensive range of standard sprinklers and spray nozzles. Besides access to those products, customers benefit from a market leading technical support team across Europe and the Middle East, which also holds regular technical training courses on water, foam, gas and detection systems, products and maintenance.

Learn more at www.viking-emea.com.

Table of contents

Standard Response Glass Bulb	3
Quick Response Glass Bulb	6
Standard Response Fusible Link	9
Quick Response Fusible Link	10
Extra Large Orifice (ELO) Sprinklers	12
K40 Standard & Quick Response Glass Bulb & Fusible Link	13
Coin™ Sprinklers	14
Stainless Steel Sprinklers	15
Spray Nozzles	17
Window Sprinklers & Nozzles	19

How to order products stating a base part number:


How to order glass bulb sprinklers							
Base part number	+	Finish code		+	Temperature (°C) code		Bulb colour
XXXXX	+	Brass	A	+	57	A	Orange
		Chrome	F		68	B	Red
		White	M-/W		79	D	Yellow
		Black	M-/B		93	E	Green
		Wax	C		141	G	Blue
		Electroless nickel PTFE (ENT)	JN		182	H	Mauve
		RAL			260	L	Black
		OPEN	Z		n/a		
Examples:		12987AE = 12987 + Brass (A) + 93°C (E)					
		12986AD = 12986 + Brass (A) + 79°C (D)					

How to order fusible link sprinklers							
Base part number	+	Finish code		+	Temperature (°C) code		Frame colour code
XXXXX	+	Brass	A	+	74	C	None
		Chrome	F		96	E	White
		White	M-/W		104	M	
		Black	M-/B		138	G	Blue
		Wax	C		141		
		RAL					
Example:		10284AC = 10284 + Brass (A) + 74°C (C)					

For all applicable approvals, please refer to the technical documentation or contact your local Viking sales office.

Standard Response | Glass Bulb

Pendent | K57 (4.2)



Base part number	10222
K-factor	K57 (4.2)
Thread size	1/2"/15 mm
SIN	VK004
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, RAL

Upright | K57 (4.2)



Base part number	10219 (1/2"), 10191 (20 mm)
K-factor	K57 (4.2)
Thread size	1/2"/15 mm
SIN	VK002
Temperatures (°C)	57, 68, 79, 93, 141, 182
Finishes	Brass, Chrome, White, Black, RAL

Pendent | K80 (5.6)



Base part number	23868 (1/2"), 23880 (15 mm)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK1021
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, RAL, ENT

Pendent | K115 (8.0)



Base part number	23876 (1/2"), 23888 (15 mm)
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK2021
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, RAL, ENT



Base part number	09992 (HP ¹)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK122
Temperatures (°C)	57, 68, 79, 93, 141, 182, 260
Finishes	Brass, Chrome, White, Black, ENT, RAL,

Upright | K80 (5.6)



Base part number	12986 (NPT), 12993 (BSP)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK100
Temperatures (°C)	57, 68, 79, 93, 141, 182, 260
Finishes	Brass, Chrome, White, Black, RAL, ENT, Wax

Upright | K115 (8.0)



Base part number	23875 (3/4"), 23887 (20 mm)
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK2001
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL



Base part number	23867 (1/2"), 23879 (15 mm)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK1001
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL



Base part number	09993 (HP ¹)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK124
Temperatures (°C)	57, 68, 79, 93, 141, 182, 260
Finishes	Brass, Chrome, White, Black, RAL

Conventional | K80 (5.6)



Base part number	23907 (1/2"), 23913 (15 mm)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK1181
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL, Wax

Conventional | K115 (8.0)




Base part number	23911 (3/4"), 23917 (20 mm)
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK1201
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL, Wax

¹ HP = High Pressure (17 bar)




Standard Response | Glass Bulb

Concealed pendent | K80 (5.6)




Base part number	24683(1/2"), 23116 (15 mm)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK4921
Temperatures (°C)	68, 93
Finishes	Brass, ENT

Vertical sidewall | K80 (5.6)




Base part number	12996 (1/2"), 12991 (15 mm)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK106
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome

Horizontal sidewall | K80 (5.6)



Base part number	12995 (1/2"), 12988 (15 mm)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK104
Temperatures (°C)	57, 68, 79, 93, 141, 182
Finishes	Brass, Chrome, White, Black, RAL, ENT

Horizontal sidewall | K80 (5.6)



Base part number	09849 (HP ¹)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK116
Temperatures (°C)	57, 68, 79, 93, 141, 182
Finishes	Brass, Chrome, White, Black, RAL, ENT

¹ HP = High Pressure (17 bar)

Standard Response | Glass Bulb

MX5 SU | Upright | K57 (4.2)



Part number	Size	Temp. (°C)	Finish
843080	3/8"/10 mm	57	Brass
843081		68	
843082		79	
843083		93	
843084		141	
843075	3/8"/10 mm	57	Chrome
843076		68	
843077		79	
843078		93	
845079		141	

MX5 SP | Pendent | K57 (4.2)



Part number	Size	Temp. (°C)	Finish
845242	3/8"/10 mm	57	Brass
845243		68	
845244		79	
845245		93	
845246		141	
845237	3/8"/10 mm	57	Chrome
845238		68	
845239		79	
845240		93	
845241		141	

MX5 FP | Flat spray pendent | K57 (4.2)



Part number	Size	Temp. (°C)	Finish
843130	3/8"/10 mm	57	Brass
843131		68	
843132		79	
843133		93	
843134		141	
843125	3/8"/10 mm	57	Chrome
843126		68	
843127		79	
843128		93	
843129		141	

MX5 SU | Upright | K80 (5.6)



Part number	Size	Temp. (°C)	Finish
843090	1/2"/15 mm	57	Brass
843091		68	
843092		79	
843093		93	
843094		141	
843085	1/2"/15 mm	57	Chrome
843086		68	
843087		79	
843088		93	
843089		141	

MX5 SU | Upright | K115 (8.0)



Part number	Size	Temp. (°C)	Finish
843100	1/2"/15 mm	57	Brass
843101		68	
843102		79	
843103		93	
843104		141	
843095	1/2"/15 mm	57	Chrome
843096		68	
843097		79	
843098		93	
845099		141	

MX5 SP | Pendent | K80 (5.6)



Part number	Size	Temp. (°C)	Finish
922113	1/2"/15 mm	57	Brass
922114		68	
922115		79	
922116		93	
922117		141	
922108	1/2"/15 mm	57	Chrome
922109		68	
922110		79	
922111		93	
922112		141	

MX5 SP | Pendent | K115 (8.0)



Part number	Size	Temp. (°C)	Finish
922128	1/2"/15 mm	57	Brass
922129		68	
922130		79	
922131		93	
922132		141	
922123	1/2"/15 mm	57	Chrome
922124		68	
922125		79	
922126		93	
922127		141	

MX5 SP | Pendent | K115 (8.0)



Part number	Size	Temp. (°C)	Finish
4000316	3/4"/20 mm	57	Brass
4000317		68	
4000318		79	
4000319		93	
4000320		141	
4000321	3/4"/20 mm	57	Chrome
4000322		68	
4000323		79	
4000324		93	
4000325		141	

MX5 SU | Upright | K115 (8.0)



Part number	Size	Temp. (°C)	Finish
4000286	3/4"/20 mm	57	Brass
4000287		68	
4000288		79	
4000289		93	
4000290		141	
4000291	3/4"/20 mm	57	Chrome
4000292		68	
4000293		79	
4000294		93	
4000295		141	

MX5 FP | Flat spray pendent | K80 (5.6)



Part number	Size	Temp. (°C)	Finish
843140	1/2"/15 mm	57	Brass
843141		68	
843142		79	
843143		93	
843144		141	
843135	1/2"/15 mm	57	Chrome
843136		68	
843137		79	
843138		93	
843139		141	

MX5 FU | Flat spray upright | K80 (5.6)



Part number	Size	Temp. (°C)	Finish
843160	1/2"/15 mm	57	Brass
843161		68	
843162		79	
843163		93	
843164		141	
843155	1/2"/15 mm	57	Chrome
843156		68	
843157		79	
843158		93	
843159		141	



Quick Response | Glass Bulb

Pendent | K57 (4.2)



Base part number	21271
K-factor	K57 (4.2)
Thread size	1/2"/15 mm
SIN	VK331
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL



Base part number	06932B
K-factor	K57 (4.2)
Thread size	3/8"/10 mm
SIN	VK3311
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, RAL

Upright | K57 (4.2)



Base part number	21269
K-factor	K57 (4.2)
Thread size	1/2"/15 mm
SIN	VK327
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL



Base part number	06931B
K-factor	K57 (4.2)
Thread size	3/8"/10 mm
SIN	VK3271
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, RAL

Pendent | K80 (5.6)



Base part number	23870 (1/2"), 23882 (15 mm)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK3021
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, RAL, ENT



Base part number	12282 (HP ¹)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK317
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL

Pendent | K115 (8.0)



Base part number	23878 (3/4"), 23890 (20 mm)
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK3521
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, RAL, ENT

Upright | K80 (5.6)



Base part number	12978
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK300
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, RAL, ENT



Base part number	23869 (1/2"), 23881 (15 mm)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK3001
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL



Base part number	12281 (HP ¹)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK315
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL

Upright | K115 (8.0)



Base part number	23877 (3/4"), 23889 (20 mm)
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK3501
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, RAL, ENT

Conventional | K80 (5.6)



Base part number	23908 (1/2"), 23914 (15 mm)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK3101
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL

Conventional | K115 (8.0)




Base part number	23912 (3/4"), 23918 (20 mm)
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK3541
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL

¹ HP = High Pressure (17 bar)


Quick Response | Glass Bulb

Concealed pendent | K57 (4.2)




Base part number	14262A (Coverplate 23447)
K-factor	K57 (4.2)
Thread size	1/2"/15 mm
SIN	VK465
Temperatures (°C)	68, 79, 93
Finishes	Brass, ENT


Concealed pendent | K80 (5.6)



Base part number	24682 (1/2"), 22962 (15 mm)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK4621
Temperatures (°C)	68, 93
Finishes	Brass, ENT




Base part number	13667A (HP ¹) (Coverplate 23447)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK463
Temperatures (°C)	68, 79, 93
Finishes	Brass, ENT



Base part number	15480A (Coverplate 23447)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK462 (MRI ²)
Temperatures (°C)	68, 79, 93
Finishes	Brass

Concealed pendent | K115 (8.0)




Base part number	13614A (Coverplate 23447)
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK464
Temperatures (°C)	68, 79, 93
Finishes	Brass, ENT




Base part number	15481A (Coverplate 23447)
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK464 (MRI ²)
Temperatures (°C)	68, 79, 93
Finishes	Brass

Horizontal sidewall | K80 (5.6)




Base part number	12997
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK305
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, RAL, ENT



Base part number	12285 (HP ¹)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK319
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome, White, Black, RAL, ENT

Horizontal sidewall | K115 (8.0)



Base part number	15591
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK360
Temperatures (°C)	57, 68, 79, 93
Finishes	Brass, Chrome, White, Black, ENT, RAL

Vertical sidewall | K57 (4.2)



Base part number	08985
K-factor	K57 (4.2)
Thread size	3/8"/10 mm
SIN	VK337
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome

Vertical sidewall | K80 (5.6)



Base part number	12983
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK306
Temperatures (°C)	57, 68, 79, 93, 141
Finishes	Brass, Chrome

¹ HP = High Pressure (17 bar) | ² MRI = Magnetic Resonance Imaging | ³ CP = Coverplate



Quick Response | Glass Bulb

MX3 SU | Upright | K57 (4.2)



Part number	Size	Temp. (°C)	Finish
843050	3/8"/10 mm	57	Brass
843051		68	
843052		79	
843053		93	
843054		141	
843045		57	Chrome
843046		68	
843047		79	
843048		93	
843049		141	

MX3 SP | Pendent | K57 (4.2)



Part number	Size	Temp. (°C)	Finish
845197	3/8"/10 mm	57	Brass
845198		68	
845199		79	
845200		93	
845201		141	
845192		57	Chrome
845193		68	
845194		79	
845195		93	
845196		141	

MX3 SU | Upright | K80 (5.6)



Part number	Size	Temp. (°C)	Finish
843060	1/2"/15 mm	57	Brass
843061		68	
843062		79	
843063		93	
843064		141	
843055		57	Chrome
843056		68	
843057		79	
843058		93	
843059		141	

MX3 SU | Upright | K115 (8.0)



Part number	Size	Temp. (°C)	Finish
843070	1/2"/15 mm	57	Brass
843071		68	
843072		79	
843073		93	
843074		141	
843065		57	Chrome
843066		68	
843067		79	
843068		93	
843069		141	

MX3 SP | Pendent | K80 (5.6)



Part number	Size	Temp. (°C)	Finish
922083	1/2"/15 mm	57	Brass
922084		68	
922085		79	
922086		93	
922087		141	
922077		57	Chrome
922078		68	
922079		79	
922080		93	
922081		141	

MX3 SP | Pendent | K115 (8.0)



Part number	Size	Temp. (°C)	Finish
922098	1/2"/15 mm	57	Brass
922099		68	
922100		79	
922101		93	
922102		141	
922093		57	Chrome
922094		68	
922095		79	
922096		93	
922097		141	

MX3 SU | Upright | K115 (8.0)



Part number	Size	Temp. (°C)	Finish
4000308	3/4"/20 mm	57	Brass
4000309		68	
4000310		79	
4000311		93	
4000312		141	
4000303		57	Chrome
4000304		68	
4000305		79	
4000306		93	
4000307		141	

MX3 SP | Pendent | K115 (8.0)



Part number	Size	Temp. (°C)	Finish
4000326	3/4"/20 mm	57	Brass
4000327		68	
4000328		79	
4000329		93	
4000330		141	
4000331		57	Chrome
4000332		68	
4000333		79	
4000334		93	
4000335		141	

MX3 FP | Flat spray pendent | K57 (4.2)



Part number	Size	Temp. (°C)	Finish
843110	1/2"/15 mm	57	Brass
843111		68	
843112		79	
843113		93	
843114		141	
843105		57	Chrome
843106		68	
843107		79	
843108		93	
843109		141	

MX3 FP | Flat spray pendent | K115 (8.0)



Part number	Size	Temp. (°C)	Finish
844593	1/2"/15 mm	57	Brass
844594		68	
844595		79	
844596		93	
844597		141	
844588		57	Chrome
844589		68	
844590		79	
844591		93	
844592		141	

MX3 FU | Flat spray upright | K80 (5.6)



Part number	Size	Temp. (°C)	Finish
843150	1/2"/15 mm	57	Brass
843151		68	
843152		79	
843153		93	
843154		141	
843145		57	Chrome
843146		68	
843147		79	
843148		93	
843149		141	

MX3 FP | Flat spray pendent | K80 (5.6)



Part number	Size	Temp. (°C)	Finish
843120	1/2"/15 mm	57	Brass
843121		68	
843122		79	
843123		93	
843124		141	
843115		57	Chrome
843116		68	
843117		79	
843118		93	
843119		141	

Quick Response | Glass Bulb

MX3 WWH Horizontal sidewall K80 (5.6)			
Part number	Size	Temp. (°C)	Finish
843972	1/2"/15 mm	57	Chrome
843973		68	
843974		79	
843975		93	
843976		141	



MX3 CCP Concealed pendent K80 (5.6)			
Part number	Size	Temp. (°C)	Finish
845911	1/2"/15 mm	68	White
845912	(standard)	93	
845851	1/2"/15 mm	68	
845852	(long)	93	Chrome
845913	1/2"/15 mm	68	
845914	(standard)	93	
845853	1/2"/15 mm	68	
845454	(long)	93	



Standard Response | Fusible Link


Pendent K57 (4.2)	
Base part number	05575
K-factor	K57 (4.2)
Thread size	1/2"/15 mm
SIN	VK008
Temperatures (°C)	74, 104, 141
Finishes	Brass, Chrome, White, Black, RAL, Wax



Upright K57 (4.2)	
Base part number	05574
K-factor	K57 (4.2)
Thread size	1/2"/15 mm
SIN	VK006
Temperatures (°C)	74, 104, 141
Finishes	Brass, Chrome, White, Black, RAL, Wax




Pendent K80 (5.6)	
Base part number	12972
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK110
Temperatures (°C)	74, 104, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL, Wax



Pendent K115 (8.0)	
Base part number	18254
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK206
Temperatures (°C)	74, 104, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL, Wax



Base part number	18256
K-factor	K115 (8.0)
Thread size	1/2"/15 mm
SIN	VK206
Temperatures (°C)	74, 104, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL, Wax



Upright K80 (5.6)	
Base part number	12973
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK108
Temperatures (°C)	74, 104, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL, Wax




Upright K115 (8.0)	
Base part number	18253
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK204
Temperatures (°C)	74, 104, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL, Wax



Base part number	18255
K-factor	K115 (8.0)
Thread size	1/2"/15 mm
SIN	VK204
Temperatures (°C)	74, 104, 141
Finishes	Brass, Chrome, White, Black, ENT, RAL, Wax



Horizontal sidewall K80 (5.6)	
Base part number	12974
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK112
Temperatures (°C)	74, 104, 141
Finishes	Brass, Chrome



Flush pendent K80 (5.6)	
Base part number	06697B
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK400
Temperatures (°C)	74, 104
Finishes	Chrome, White





Quick Response | Fusible Link

Pendent | K57 (4.2)



Base part number	21272
K-factor	K57 (4.2)
Thread size	1/2"/15 mm
SIN	VK332
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, ENT, RAL

Upright | K57 (4.2)



Base part number	21270
K-factor	K57 (4.2)
Thread size	1/2"/15 mm
SIN	VK328
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, ENT, RAL

Pendent | K80 (5.6)



Base part number	17536
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK303
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, ENT, RAL

Pendent | K115 (8.0)



Base part number	18274
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK353
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, RAL



Base part number	13954 (HP ¹)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK318
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, ENT, RAL



Base part number	18273
K-factor	K115 (8.0)
Thread size	1/2"/15 mm
SIN	VK353
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, RAL

Upright | K80 (5.6)



Base part number	17535
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK301
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, ENT, RAL

Upright | K115 (8.0)



Base part number	18275
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK351
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, ENT, RAL



Base part number	13953 (HP ¹)
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK316
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, ENT, RAL



Base part number	18272
K-factor	K115 (8.0)
Thread size	1/2"/15 mm
SIN	VK351
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, ENT, RAL

Conventional | K80 (5.6)



Base part number	19392
K-factor	K80 (5.6)
Thread size	1/2"/15 mm
SIN	VK311
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, RAL


Conventional | K115 (8.0)





Base part number	18276
K-factor	K115 (8.0)
Thread size	3/4"/20 mm
SIN	VK355
Temperatures (°C)	74, 96, 138
Finishes	Brass, Chrome, White, Black, RAL


¹ HP = High Pressure (17 bar)

Quick Response | Fusible Link

Horizontal sidewall K80 (5.6)	
	Base part number 13949
	K-factor K80 (5.6)
	Thread size 1/2"/15 mm
	SIN VK308
	Temperatures (°C) 74, 96, 138
	Finishes Brass, Chrome, White, Black, RAL

Horizontal sidewall K80 (5.6)	
	Base part number 13955 (HP ¹)
	K-factor K80 (5.6)
	Thread size 1/2"/15 mm
	SIN VK320
	Temperatures (°C) 74, 96, 138
	Finishes Brass, Chrome, White, Black, ENT, RAL


Concealed horizontal sidewall K80 (5.6)	
	Base part number 17555
	K-factor K80 (5.6)
	Thread size 1/2"/15 mm
	SIN VK481
	Temperatures (°C) 74, 104
	Finishes Brass, Chrome, White, Black


Vertical sidewall K80 (5.6)	
	Base part number 13951
	K-factor K80 (5.6)
	Thread size 1/2"/15 mm
	SIN VK309
	Temperatures (°C) 74, 96, 138
	Finishes Brass, Chrome

¹ HP = High Pressure (17 bar)





Standard Response | Glass Bulb | Extra Large Orifice (ELO)


Pendent K161 (11.2)	
	Base part number 17961 (3/4"), 14820 (20 mm) K-factor K161 (11.2) Thread size 3/4"/20 mm SIN VK536 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, RAL, ENT, Wax


Upright K161 (11.2)	
	Base part number 09679 (3/4"), 14819 (20 mm) K-factor K161 (11.2) Thread size 3/4"/20 mm SIN VK530 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, RAL, ENT, Wax


Quick Response | Glass Bulb | Extra Large Orifice (ELO)

Pendent K161 (11.2)	
	Base part number 08337 K-factor K161 (11.2) Thread size 3/4"/20 mm SIN VK377 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, RAL, ENT


Pendent K161 (11.2)	
	Base part number 17489 K-factor K161 (11.2) Thread size 1/2"/15 mm SIN VK377 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, RAL, ENT


Upright K161 (11.2)	
	Base part number 10633 K-factor K161 (11.2) Thread size 3/4"/20 mm SIN VK531 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, RAL, ENT

	Base part number 19305 K-factor K161 (11.2) Thread size 1/2"/15 mm SIN VK5311 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, RAL
---	--


	Base part number 19304 K-factor K161 (11.2) Thread size 3/4"/20 mm SIN VK5311 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, RAL
---	--


Quick Response | Fusible Link | Extra Large Orifice (ELO)


Concealed pendent K161 (11.2)	
	Base part number 15764A (Coverplate 23495) K-factor K161 (11.2) Thread size 3/4"/20 mm SIN VK469 Temperatures (°C) 74, 96 Finishes Chrome, White, Black, RAL


Upright K161 (11.2)	
	Base part number 13978 K-factor K161 (11.2) Thread size 3/4"/20 mm SIN VK533 Temperatures (°C) 74, 96, 138 Finishes Brass, Chrome, White, Black, RAL


Standard Response | Glass Bulb | K40


Pendent K40 (2.8)	
	Base part number 12994 K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK003 Temperatures (°C) 57, 68, 79, 93, 141, 182 Finishes Brass, Chrome, White, Black, RAL, Wax

Pendent K40 (2.8)	
	Base part number 09994 (HP ¹) K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK023 Temperatures (°C) 57, 68, 79, 93 Finishes Brass, Chrome, White, Black, RAL


Upright K40 (2.8)	
	Base part number 13006 K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK001 Temperatures (°C) 57, 68, 79, 93, 141, 182 Finishes Brass, Chrome, White, Black, RAL, Wax


Upright K40 (2.8)	
	Base part number 09995 (HP ¹) K-factor K40 (2.8) Thread size 1/2"/20 mm SIN VK021 Temperatures (°C) 57, 68, 79, 93, 141, 182 Finishes Brass, Chrome, White, Black, RAL


Concealed pendent K40 (2.8)	
	Base part number 13831A (Coverplate 23447) K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK461 Temperatures (°C) 68, 79, 93 Finishes Brass, Chrome, White, Black, RAL


Horizontal sidewall K40 (2.8)	
	Base part number 09997 K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK015 Temperatures (°C) 57, 68, 79, 93, 141, 182 Finishes Brass, Chrome, White, Black, RAL


Quick Response | Glass Bulb | K40


Pendent K40 (2.8)	
	Base part number 20984 K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK329 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, ENT, RAL

Pendent K40 (2.8)	
	Base part number 20993 (HP ¹) K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK342 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, ENT, RAL

Upright K40 (2.8)	
	Base part number 20982 K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK325 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, ENT, RAL

Upright K40 (2.8)	
	Base part number 20991 (HP ¹) K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK340 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, ENT, RAL


Horizontal sidewall K40 (2.8)	
	Base part number 20989 K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK333 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, ENT, RAL


Horizontal sidewall K40 (2.8)	
	Base part number 20995 (HP ¹) K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK344 Temperatures (°C) 57, 68, 79, 93, 141 Finishes Brass, Chrome, White, Black, ENT, RAL


¹ HP = High Pressure (17 bar)





Quick Response | Fusible Link | K40


Pendent K40 (2.8)	
	Base part number 13959 K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK330 Temperatures (°C) 74, 96, 138 Finishes Brass, Chrome, White, Black, ENT, RAL

Pendent K40 (2.8)	
	Base part number 13964 (HP ¹) K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK343 Temperatures (°C) 74, 96, 138 Finishes Brass, Chrome, White, Black, ENT, RAL


Upright K40 (2.8)	
	Base part number 20983 K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK326 Temperatures (°C) 74, 96, 138 Finishes Brass, Chrome, White, Black, ENT, RAL


Upright K40 (2.8)	
	Base part number 20992 (HP ¹) K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK341 Temperatures (°C) 74, 96, 138 Finishes Brass, Chrome, White, Black, ENT, RAL

Horizontal sidewall K40 (2.8)	
	Base part number 20990 K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK334 Temperatures (°C) 74, 96, 138 Finishes Brass, Chrome, White, Black, ENT, RAL


Horizontal sidewall K40 (2.8)	
	Base part number 20996 (HP ¹) K-factor K40 (2.8) Thread size 1/2"/15 mm SIN VK346 Temperatures (°C) 74, 96, 138 Finishes Brass, Chrome, White, Black, ENT, RAL

Quick Response | Glass Bulb | COIN™

Upright K57 (4.2)	
	Base part number 12493 K-factor K57 (4.2) Thread size 1/2"/15 mm SIN VK900 Temperatures (°C) 79 Finishes Brass, ENT


Upright K80 (5.6)	
	Base part number 20757 K-factor K80 (5.6) Thread size 1/2"/15 mm SIN VK950 Temperatures (°C) 93 Finishes Brass, ENT


Quick Response | Fusible Link | COIN™


Upright K57 (4.2)	
	Base part number 12676AE K-factor K57 (4.2) Thread size 1/2"/15 mm SIN VK901 Temperatures (°C) 96 Finishes Brass, ENT


¹ HP = High Pressure (17 bar)


Stainless Steel | Standard Response | Glass Bulb


Pendent K80 (5.6)	
	Base part number 06483B K-factor K80 (5.6) Thread size 1/2"/15 mm SIN VK132 Temperatures (°C) 57, 68, 79, 93, 141, 182, 260 Finishes Stainless steel, Wax


Upright K80 (5.6)	
	Base part number 05012B K-factor K80 (5.6) Thread size 1/2"/15 mm SIN VK130 Temperatures (°C) 57, 68, 79, 93, 141, 182, 260 Finishes Stainless steel, Wax


MX5 SP Pendent K57 (4.2)				
	Part number	Size	Temp. (°C)	Finish
	845247	3/8"/10 mm	57	Stainless
	845248		68	
	845249		79	
	845250		93	
	845251		141	


MX5 SU Upright K57 (4.2)				
	Part number	Size	Temp. (°C)	Finish
	845006	3/8"/10 mm	57	Stainless
	845007		68	
	845008		79	
	845009		93	
	845010		141	


MX5 FP Flat spray pendent K57 (4.2)				
	Part number	Size	Temp. (°C)	Finish
	844917	3/8"/10 mm	57	Stainless
	844918		68	
	844919		79	
	844920		93	
	844921		141	


MX5 SP Pendent K80 (5.6)				
	Part number	Size	Temp. (°C)	Finish
	922118	1/2"/15 mm	57	Stainless
	922119		68	
	922120		79	
	922121		93	
	922122		141	

MX5 SU Upright K80 (5.6)				
	Part number	Size	Temp. (°C)	Finish
	845011	1/2"/15 mm	57	Stainless
	845012		68	
	845013		79	
	845014		93	
	845015		141	

MX5 FP Flat spray pendent K80 (5.6)				
	Part number	Size	Temp. (°C)	Finish
	844922	1/2"/15 mm	57	Stainless
	844923		68	
	844924		79	
	844925		93	
	844926		141	


MX5 FU Flat spray upright K80 (5.6)				
	Part number	Size	Temp. (°C)	Finish
	845056	1/2"/15 mm	57	Stainless
	845057		68	
	845058		79	
	845059		93	
	845060		141	


MX5 SP Pendent K115 (8.0)				
	Part number	Size	Temp. (°C)	Finish
	922133	1/2"/15 mm	57	Stainless
	922134		68	
	922135		79	
	922136		93	
	922137		141	


MX5 SU Upright K115 (8.0)				
	Part number	Size	Temp. (°C)	Finish
	845016	1/2"/15 mm	57	Stainless
	845017		68	
	845018		79	
	845019		93	
	845020		141	





Stainless Steel | Quick Response | Glass Bulb


Pendent K80 (5.6)													
	<table border="1"> <tr><td>Base part number</td><td>14692</td></tr> <tr><td>K-factor</td><td>K80 (5.6)</td></tr> <tr><td>Thread size</td><td>1/2"/15 mm</td></tr> <tr><td>SIN</td><td>VK339</td></tr> <tr><td>Temperatures (°C)</td><td>57, 68, 79, 93, 141</td></tr> <tr><td>Finishes</td><td>Stainless steel</td></tr> </table>	Base part number	14692	K-factor	K80 (5.6)	Thread size	1/2"/15 mm	SIN	VK339	Temperatures (°C)	57, 68, 79, 93, 141	Finishes	Stainless steel
Base part number	14692												
K-factor	K80 (5.6)												
Thread size	1/2"/15 mm												
SIN	VK339												
Temperatures (°C)	57, 68, 79, 93, 141												
Finishes	Stainless steel												


Upright K80 (5.6)													
	<table border="1"> <tr><td>Base part number</td><td>14693</td></tr> <tr><td>K-factor</td><td>K80 (5.6)</td></tr> <tr><td>Thread size</td><td>1/2"/15 mm</td></tr> <tr><td>SIN</td><td>VK338</td></tr> <tr><td>Temperatures (°C)</td><td>57, 68, 79, 93, 141</td></tr> <tr><td>Finishes</td><td>Stainless steel</td></tr> </table>	Base part number	14693	K-factor	K80 (5.6)	Thread size	1/2"/15 mm	SIN	VK338	Temperatures (°C)	57, 68, 79, 93, 141	Finishes	Stainless steel
Base part number	14693												
K-factor	K80 (5.6)												
Thread size	1/2"/15 mm												
SIN	VK338												
Temperatures (°C)	57, 68, 79, 93, 141												
Finishes	Stainless steel												


MX3 SP Pendent K57 (4.2)				
	Part number	Size	Temp. (°C)	Finish
	845202	3/8"/10 mm	57	Stainless
	845203		68	
	845204		79	
	845205		93	
	845206		141	


MX3 SU Upright K57 (4.2)				
	Part number	Size	Temp. (°C)	Finish
	844070	3/8"/10 mm	57	Stainless
	844071		68	
	844072		79	
	844073		93	
	844074		141	


MX3 FP Flat spray pendent K57 (4.2)				
	Part number	Size	Temp. (°C)	Finish
	844927	3/8"/10 mm	57	Stainless
	844928		68	
	844929		79	
	844930		93	
	844931		141	


MX3 FU Flat spray upright K80 (5.6)				
	Part number	Size	Temp. (°C)	Finish
	845051	1/2"/15 mm	57	Stainless
	845052		68	
	845053		79	
	845054		93	
	845055		141	


MX3 SP Pendent K80 (5.6)				
	Part number	Size	Temp. (°C)	Finish
	922088	1/2"/15 mm	57	Stainless
	922089		68	
	922090		79	
	922091		93	
	922092		141	

MX3 SU Upright K80 (5.6)				
	Part number	Size	Temp. (°C)	Finish
	844075	1/2"/15 mm	57	Stainless
	844076		68	
	844077		79	
	844078		93	
	844079		141	


MX3 WWH Horizontal sidewall K80 (5.6)				
	Part number	Size	Temp. (°C)	Finish
	844065	1/2"/15 mm	57	Stainless
	844066		68	
	844067		79	
	844068		93	
	844069		141	

MX3 FP Flat spray pendent K80 (5.6)				
	Part number	Size	Temp. (°C)	Finish
	844932	1/2"/15 mm	57	Stainless
	844933		68	
	844934		79	
	844935		93	
	844936		141	

MX3 SP Pendent K115 (8.0)				
	Part number	Size	Temp. (°C)	Finish
	922103	1/2"/15 mm	57	Stainless
	922104		68	
	922105		79	
	922106		93	
	922107		141	

MX3 SU Upright K115 (8.0)				
	Part number	Size	Temp. (°C)	Finish
	844080	1/2"/15 mm	57	Stainless
	844081		68	
	844082		79	
	844083		93	
	844084		141	

Spray Nozzles



Frame style solid cone automatic or open						
SIN	Angle	K-factor	Part number	Thread	Temp.	Finishes
N/A	60°	20 (1.4)	21381	1/2"/15 mm	57 68 79 93 141 Open (Z)	Brass Black PTFE
		27 (1.9)	21377			
		40 (2.8)	21373			
		57 (4.2)	21369			
		80 (5.6)	21365			
	90°	20 (1.4)	21382			
		27 (1.9)	21378			
		40 (2.8)	21374			
		57 (4.2)	21370			
		80 (5.6)	21366			
	120°	20 (1.4)	21383			
		27 (1.9)	21379			
		40 (2.8)	21375			
		57 (4.2)	21371			
		80 (5.6)	21367			
	150°	20 (1.4)	21384			
		27 (1.9)	21380			
		40 (2.8)	21376			
		57 (4.2)	21372			
		80 (5.6)	21368			



Model A, B, C & D solid cone open (medium-high velocity)						
SIN	Angle	K-factor	Part number	Thread	Temp.	Finishes
VK740	30°	17 (1.2)	05133A_J	1/2"/15 mm		Brass: Replace "_" with "A" ENT: Replace "_" with "J"
VK750		29 (2.0)	05134A_J			
VK760		40 (2.8)	05135A_J			
VK770		57 (4.2)	19505_J			
VK780		62 (4.3)	19506_J			
VK741	60°	17 (1.2)	05133A_K			
VK751		29 (2.0)	05134A_K			
VK761		40 (2.8)	05135A_K			
VK771		57 (4.2)	19505_K			
VK781		62 (4.3)	19506_K			
VK742	90°	17 (1.2)	05133A_L			
VK752		29 (2.0)	05134A_L			
VK762		40 (2.8)	05135A_L			
VK772		57 (4.2)	19505_L			
VK782		62 (4.3)	19506_L			
VK743	120°	17 (1.2)	05133A_M			
VK753		29 (2.0)	05134A_M			
VK763		40 (2.8)	05135A_M			
VK773		57 (4.2)	19505_M			
VK783		62 (4.3)	19506_M			
VK744	140°	17 (1.2)	05133A_N			
VK754		29 (2.0)	05134A_N			
VK764		40 (2.8)	05135A_N			
VK774		57 (4.2)	19505_N			
VK784		62 (4.3)	19506_N			



Spray Nozzles



Model E solid cone open (low-medium velocity)					
SIN	Angle	K-factor	Part number	Thread	Finishes
VK810	65°	17 (1.2)	12873_Z	1/2"/15 mm	Brass: Replace "_" with "A" ENT: Replace "_" with "J"
		26 (1.8)	12872_Z		
		33 (2.3)	12871_Z		
		46 (3.2)	12870_Z		
		59 (4.1)	12869_Z		
		80 (5.6)	12868_Z		
		104 (7.2)	12867_Z		
VK811	80°	17 (1.2)	12880_Z		
		26 (1.8)	12879_Z		
		33 (2.3)	12878_Z		
		46 (3.2)	12877_Z		
		59 (4.1)	12876_Z		
		80 (5.6)	12875_Z		
		104 (7.2)	12874_Z		
VK812	95°	17 (1.2)	12887_Z		
		26 (1.8)	12886_Z		
		33 (2.3)	12885_Z		
		46 (3.2)	12884_Z		
		59 (4.1)	12883_Z		
		80 (5.6)	12882_Z		
		104 (7.2)	12881_Z		
VK813	110°	17 (1.2)	12894_Z		
		26 (1.8)	12893_Z		
		33 (2.3)	12892_Z		
		46 (3.2)	12891_Z		
		59 (4.1)	12890_Z		
		80 (5.6)	12889_Z		
		104 (7.2)	12888_Z		
VK814	125°	17 (1.2)	12901_Z		
		26 (1.8)	12900_Z		
		33 (2.3)	12899_Z		
		46 (3.2)	12898_Z		
		59 (4.1)	12897_Z		
		80 (5.6)	12896_Z		
		104 (7.2)	12895_Z		
VK815	140°	17 (1.2)	12908_Z		
		26 (1.8)	12907_Z		
		33 (2.3)	12906_Z		
		46 (3.2)	12905_Z		
		59 (4.1)	12904_Z		
		80 (5.6)	12903_Z		
		104 (7.2)	12902_Z		
VK816	160°	17 (1.2)	12915_Z		
		26 (1.8)	12914_Z		
		33 (2.3)	12913_Z		
		46 (3.2)	12912_Z		
		59 (4.1)	12911_Z		
		80 (5.6)	12910_Z		
		104 (7.2)	12909_Z		
VK817	180°	17 (1.2)	12922_Z		
		26 (1.8)	12921_Z		
		33 (2.3)	12920_Z		
		46 (3.2)	12919_Z		
		59 (4.1)	12918_Z		
		80 (5.6)	12917_Z		
		104 (7.2)	12916_Z		

Spray Nozzles



RD21 frame style	K-factor	Part number Brass	Part number Stainless
	14 (0.98)	844800	844807
	20 (1.4)	844801	844808
	28 (1.9)	844802	844809
	46 (3.2)	844803	844810
	57 (3.7)	844804	844811
	80 (5.6)	844805	844812
115 (8.0)	844806	844813	



MXD-SD solid cone	K-factor	Part number Brass	Part number Stainless
	20 (1.4)	122395	845489
	28 (1.9)	845486	845490
	40 (2.8)	845487	845491
57 (3.7)	845488	845492	


Window Sprinklers & Nozzles

Vertical sidewall, pendent | K80 (5.6)



Base part number	23828 (NPT), 23829 (BSPT)
K-factor	K80.6 (5.6)
Thread size	1/2" (NPT), 15 mm (BSPT)
SIN	VK960
Temperatures (°C)	68, 93
Finishes	Brass, Chrome, White Polyester, Black Polyester, ENT

Horizontal sidewall | K80 (5.6)



Base part number	23830 (NPT), 23831 (BSPT)
K-factor	K80.6 (5.6)
Thread size	1/2" (NPT), 15 mm (BSPT)
SIN	VK962
Temperatures (°C)	68, 93
Finishes	Brass, Chrome, White Polyester, Black Polyester, ENT

Model C-1 window nozzle



SIN	K-factor	Part number	Thread	Finishes
VK790	22 (1.5)	01320B_	1/2"/15 mm	Brass: Replace " _ " with "A" ENT: Replace " _ " with "J"
VK791	30 (2.1)	01321B_		
VK792	43 (3.0)	01322B_		
VK793	62 (4.3)	01323B_		
VK794	84 (5.8)	01324B_	3/4"/20 mm	
VK795	105 (7.3)	01325B_		
VK796	117 (8.1)	01326B_		

Model A, B, C & D dust covers



K-factor	Part number	Material
17-47 (1.2-3.2)	02409A	Polyethylene
53-71 (4.1-4.9)	02410A	

Model E blow-off plugs



K-factor	Part number	Material
17, 26, 33 (1.2, 1.8, 2.3)	13161	EPDM rubber
46 (3.2)	13159	
59 (4.1)	13160	
80 (5.6)	13161	
104 (7.2)	13162	



MXD-WD window nozzle	K-factor	Part number Brass	Part number Stainless
	1.7 (0.1)	217470	841863
	16 (1.1)	131170	841864
	20 (1.4)	131182	841865
	25 (1.7)	131194	841866
	32 (2.2)	131200	841867
	40 (2.9)	131212	841868
	50 (3.6)	131224	841869
60 (4.2)	131236	841870	

Europe, Middle East & Africa

BENELUX

Viking SupplyNet bv
Eekboerstraat 28b-3
NL-7575 AX Oldenzaal
Netherlands
Tel.: +31 (0)541 573233
vikingnetherlands@viking-emea.com

CENTRAL & EASTERN EUROPE

Viking GmbH
Industriestr. 10/12
D-23840 Bad Oldesloe
Germany
Tel.: +49 (0)4531 803 8087
vikinggermany@viking-emea.com

FRANCE

Sprinkler Viking France S.à r.l.
Centre d'Affaires CESCO
4, rue Marconi
BP 25180
F-57075 Metz Cedex 03
France
Tel.: +33 (0)800 10 29 23
vikingfrance@viking-emea.com

IBÉRICA

Viking Sprinkler S.A.
Calle Picos de Europa 4A
San Fernando de Henares
E-28830 Madrid
Spain
Tel.: +34 91 677 8352
vikingiberica@viking-emea.com

ITALY

Viking Italia S.r.l.
Via Pavia, 76
I-27042 Bressana Bottarone (PV)
Italy
Tel.: +39-(0)2- 30550778
vikingitaly@viking-emea.com

MIDDLE EAST

Viking Arabia FZE
LOB 19 Office #2007
Post Box No. 17531
Jebel Ali Free Zone, Dubai
United Arab Emirates
Tel.: +971 (0)4 8895 561
vikingdubai@viking-emea.com

NORDIC

Viking Nordic AB
Staffans Väg 5
S-192 78 Sollentuna
Sweden
Tel.: +46 (0)8 594 415 90
vikingsweden@viking-emea.com

POLAND

Viking SupplyNet Sp. z o.o.
ul. Żelazna 59
PL-00 848 Warsaw
Poland
Tel.: +48 22 103 30 54
vikingpoland@viking-emea.com

ROMANIA & BULGARIA

Viking Romania S.r.l.
Strada Vulturilor 18-18A, cam 3
The LOBBY
RO-030855 Bucharest
Romania
Tel.: +40 21 311 51 48
vikingromania@viking-emea.com

TURKEY

Viking Turkey Yangın Korunum Sistemleri Ticaret A.Ş.
Sahrayıcedit Mah. Halk Sokak
Golden Plaza C Blok No:29, Kat:4, Daire:8
Sahrayı Cedit, Kadıköy - 34734 İstanbul
Turkey
Tel.: +90 (0)216 403 18 00
vikingturkey@viking-emea.com

UK & IRELAND

Viking SupplyNet Ltd.
Unit 2 - Byram House, Newborn Court
Chapel Street
Epworth DN9 1HQ
United Kingdom
Tel.: +44 (0)1427 871 000
vikinguk@viking-emea.com

For further information,
please visit
www.viking-emea.com



For further information, please contact your local Viking sales office or refer to the technical documentation.
The contents of this publication are subject to modifications without notice.

Photo
Cover: Fotolia © gemenacom

Trusted above all.

Viking S.A. | 21, Z.I. Haneboesch, L-4562 Differdange / Niederkorn, Luxembourg | Tel.: +352 58 37 37 - 1, vikinglux@viking-emea.com

