








Foam Storage Tanks | Foam Bladder Tank | VFT Vertical Carbon Steel - 12 bar or 16 bar - ASME FM/UL



SPECIFICATIONS	
Related Documents	TD1.3.1.1 (Technical Data Page)
Approvals	    
Design Code	In accordance with ASME Sec.VIII Div1
Design Pressure	175 psi (12.1 bar) or 232 psi (16.0 bar)
Volume	25 USG (94 l) to 4,000 USG (15,141 l)
Material (Tank)	Carbon steel
Material (Bladder)	Polyester reinforced hypalon-neoprene polymer or NBR
Finish	Red epoxy (Flame red RAL3000)
Weight	See technical data page
Options	<ul style="list-style-type: none"> • Pre-piped with proportioner • Additional protective coatings • Ladder, platform, sunshade • Skid mounting See technical data page for complete list
<p>Note: Bladder tank is FM Approved and/or UL Listed as part of a fire extinguishing system combining designated foam concentrates, ratio controllers, ILBP's and discharge devices. Approved and Listed system components can be found at www.approvalguide.com and https://iq.ulprospector.com Bladder tanks are tested for compatibility with specific foam concentrates as per the technical data page.</p>	

Part number		Volume		Part number		Volume	
12.1 bar	16 bar	USG	Litres	12.1 bar	16 bar	USG	Litres
VFTV0025GAF	VFTV0025GAF-16	25	94	VFTV1200GAF	VFTV1200GAF-16	1,200	4,542
VFTV0036GAF	VFTV0036GAF-16	36	136	VFTV1300GAF	VFTV1300GAF-16	1,300	4,921
VFTV0050GAF	VFTV0050GAF-16	50	189	VFTV1400GAF	VFTV1400GAF-16	1,400	5,299
VFTV0075GAF	VFTV0075GAF-16	75	283	VFTV1500GAF	VFTV1500GAF-16	1,500	5,678
VFTV0100GAF	VFTV0100GAF-16	100	378	VFTV1600GAF	VFTV1600GAF-16	1,600	6,056
VFTV0150GAF	VFTV0150GAF-16	150	567	VFTV1700GAF	VFTV1700GAF-16	1,700	6,435
VFTV0200GAF	VFTV0200GAF-16	200	757	VFTV1800GAF	VFTV1800GAF-16	1,800	6,813
VFTV0250GAF	VFTV0250GAF-16	250	946	VFTV1900GAF	VFTV1900GAF-16	1,900	7,192
VFTV0300GAF	VFTV0300GAF-16	300	1,135	VFTV2000GAF	VFTV2000GAF-16	2,000	7,570
VFTV0350GAF	VFTV0350GAF-16	350	1,324	VFTV2200GAF	VFTV2200GAF-16	2,200	8,327
VFTV0400GAF	VFTV0400GAF-16	400	1,514	VFTV2400GAF	VFTV2400GAF-16	2,400	9,084
VFTV0450GAF	VFTV0450GAF-16	450	1,703	VFTV2600GAF	VFTV2600GAF-16	2,600	9,842
VFTV0500GAF	VFTV0500GAF-16	500	1,892	VFTV2800GAF	VFTV2800GAF-16	2,800	10,599
VFTV0600GAF	VFTV0600GAF-16	600	2,271	VFTV3000GAF	VFTV3000GAF-16	3,000	11,356
VFTV0700GAF	VFTV0700GAF-16	700	2,649	VFTV3200GAF	VFTV3200GAF-16	3,200	12,113
VFTV0800GAF	VFTV0800GAF-16	800	3,028	VFTV3400GAF	VFTV3400GAF-16	3,400	12,870
VFTV0900GAF	VFTV0900GAF-16	900	3,406	VFTV3600GAF	VFTV3600GAF-16	3,600	13,627
VFTV1000GAF	VFTV1000GAF-16	1,000	3,785	VFTV3800GAF	VFTV3800GAF-16	3,800	14,384
VFTV1100GAF	VFTV1100GAF-16	1,100	4,163	VFTV4000GAF	VFTV4000GAF-16	4,000	15,141

Note: This document contains basic product information only. Information, photos and drawings are not contractually binding. In all cases, the manufacturer's full technical documentation (see "Related Documents" above) remains the reference document. Note that certificates, test reports and approvals may be published in the OEM name. The contents of this publication are subject to modifications without notice. All rights reserved.

Trusted above all.

