








Foam Storage Tanks | Foam Bladder Tank | VFT Vertical Stainless Steel - 12 bar or 16 bar - ASME U-1A FM/UL



Image for illustration purposes only. Standard finish is painted flame red RAL3000. Natural finish available on special request.

SPECIFICATIONS	
Related Documents	TD1.3.1.5 (Technical Data Page)
Approvals	    
Design Code	ASME Sec.VIII Div1 with U-1A "U stamp"
Design Pressure	175 psi (12.1 bar) or 232 psi (16.0 bar)
Volume	25 USG (94 l) to 4,000 USG (15,141 l)
Material (Tank)	Stainless steel
Material (Bladder)	Polyester reinforced hypalon-neoprene polymer or NBR
Finish	Red epoxy (Flame red RAL3000)
Weight	See technical data page
Options	<ul style="list-style-type: none"> • Pre-piped with proportioner • Additional protective coatings • Ladder, platform, sunshade • Skid mounting See technical data page for complete list
<p>Note: Bladder tank is FM Approved and/or UL Listed as part of a fire extinguishing system combining designated foam concentrates, ratio controllers, ILBP's and discharge devices. Approved and Listed system components can be found at www.approvalguide.com and https://iq.ulprospector.com Bladder tanks are tested for compatibility with specific foam concentrates as per the technical data page.</p>	

Part number		Volume		Part number		Volume	
12.1 bar	16 bar	USG	Litres	12.1 bar	16 bar	USG	Litres
VFTV0025U-ST	VFTV0025U-16-ST	25	94	VFTV1200U-ST	VFTV1200U-16-ST	1,200	4,542
VFTV0036U-ST	VFTV0036U-16-ST	36	136	VFTV1300U-ST	VFTV1300U-16-ST	1,300	4,921
VFTV0050U-ST	VFTV0050U-16-ST	50	189	VFTV1400U-ST	VFTV1400U-16-ST	1,400	5,299
VFTV0075U-ST	VFTV0075U-16-ST	75	283	VFTV1500U-ST	VFTV1500U-16-ST	1,500	5,678
VFTV0100U-ST	VFTV0100U-16-ST	100	378	VFTV1600U-ST	VFTV1600U-16-ST	1,600	6,056
VFTV0150U-ST	VFTV0150U-16-ST	150	567	VFTV1700U-ST	VFTV1700U-16-ST	1,700	6,435
VFTV0200U-ST	VFTV0200U-16-ST	200	757	VFTV1800U-ST	VFTV1800U-16-ST	1,800	6,813
VFTV0250U-ST	VFTV0250U-16-ST	250	946	VFTV1900U-ST	VFTV1900U-16-ST	1,900	7,192
VFTV0300U-ST	VFTV0300U-16-ST	300	1,135	VFTV2000U-ST	VFTV2000U-16-ST	2,000	7,570
VFTV0350U-ST	VFTV0350U-16-ST	350	1,324	VFTV2200U-ST	VFTV2200U-16-ST	2,200	8,327
VFTV0400U-ST	VFTV0400U-16-ST	400	1,514	VFTV2400U-ST	VFTV2400U-16-ST	2,400	9,084
VFTV0450U-ST	VFTV0450U-16-ST	450	1,703	VFTV2600U-ST	VFTV2600U-16-ST	2,600	9,842
VFTV0500U-ST	VFTV0500U-16-ST	500	1,892	VFTV2800U-ST	VFTV2800U-16-ST	2,800	10,599
VFTV0600U-ST	VFTV0600U-16-ST	600	2,271	VFTV3000U-ST	VFTV3000U-16-ST	3,000	11,356
VFTV0700U-ST	VFTV0700U-16-ST	700	2,649	VFTV3200U-ST	VFTV3200U-16-ST	3,200	12,113
VFTV0800U-ST	VFTV0800U-16-ST	800	3,028	VFTV3400U-ST	VFTV3400U-16-ST	3,400	12,870
VFTV0900U-ST	VFTV0900U-16-ST	900	3,406	VFTV3600U-ST	VFTV3600U-16-ST	3,600	13,627
VFTV1000U-ST	VFTV1000U-16-ST	1,000	3,785	VFTV3800U-ST	VFTV3800U-16-ST	3,800	14,384
VFTV1100U-ST	VFTV1100U-16-ST	1,100	4,163	VFTV4000U-ST	VFTV4000U-16-ST	4,000	15,141

Note: This document contains basic product information only. Information, photos and drawings are not contractually binding. In all cases, the manufacturer's full technical documentation (see "Related Documents" above) remains the reference document. Note that certificates, test reports and approvals may be published in the OEM name. The contents of this publication are subject to modifications without notice. All rights reserved.

Trusted above all.

