





Proportioning Devices | ILPB/Balanced Proportioners | PB Balanced Proportioner



SPECIFICATIONS	
Related Documents	None available
Approvals	
Material	Bronze or stainless steel
Connection Type	Wafer
Max. Working pressure	20 bar
Minimum Foam-Water Pressure Difference	1-1.5 bar
Weight	See table



Part number - Bronze	Part number - Stainless steel	Dimensions				Flow rate Q -		Foam type	Pressure drop @ maxQ Bar	Weight (kg)
		A (mm)	ØB	C (mm)	ØD	min. l/min	max. l/min			
Standard version - RUS certified										
EPB03Z	EPB03X	259	3" / DN80	70	2" / DN50	400	4,000	Various. Please contact us to verify.	2.0	30.0
EPB04Z	EPB04X	259	4" / DN100	70	2" / DN50	400	4,000		2.0	30.0
EPB06Z	EPB06X	291	6" / DN150	70	2" / DN50	840	8,400		3.2	38.0
EPB08Z	EPB08X	361	8" / DN200	82	3" / DN80	1,600	16,000		2.4	54.0
EPB10Z	EPB10X	393	10" / DN250	82	3" / DN80	2,500	25,000		2.5	62.0

<sup>1</sup> The PB can work at higher flowrates with larger pressure drop

Note: This document contains basic product information only. Information, photos and drawings are not contractually binding. In all cases, the manufacturer's full technical documentation (see "Related Documents" above) remains the reference document. Note that certificates, test reports and approvals may be published in the OEM name. The contents of this publication are subject to modifications without notice. All rights reserved

Trusted above all.

